

BET-202

Application

Industrial Applications 、 Aerospace
Pressure vessel 、 Pipe & tube fabrication
Food process 、 Vacuum equipment

Features

Lightweight and portability for outside job
Inverter technology for energy-efficient
Thermal Overload Protection
Excellent spot welding effect
pulse wave function
Can be matched with automated welding
Built-in adjustable arc properties
Support contact arc starting & automatic arc closing function



Specification

Input Power	V	-	Pre flow time	Sec	-
		220 V ,1Φ	Post flow time	Sec	2~10
Input voltage range	%	±15%	Pulse current	A	-
Input frequency	HZ	50&60	Pulse frequency	HZ	High: 10
Rated input capacity	KVA	6			-
	KW	4.73			Low: 1
Rated output	V	18	Pulse Ratio Width	%	50
	A	200	Duty cycle	-	200A / 40%
					126A / 100%
Welding amperage range	A	3~200	Water cooler control	-	-
			Clean	A	-
			Gas check	-	-
Efficiency	%	72	Crater control	-	Crater
Open-circuit voltage	V	100	Insulation class	-	H
Up slope	Sec	-	Protection class	-	IP21S
Down slope	Sec	0.1~5	Dimension (W*D*H)	mm	430*225*360
Spot time	Sec	-	Net Weight	kg	16

