

HW2000-2

Application

General Industry : Sheet metal cabinets / kitchen & bath / construction / hardware tools

Precision Technology : Electronics / medical / molds / new energy

Heavy Transpor : Automotive / aerospace / rail equipment

Features

Core Brand : Raycus laser + RelFar torch + S&A-temp chiller for high output, long-term stability, and industrial reliability.

4-in-1 Function : Welding / Cutting / Cleaning / Rust Removal—fast switching for flexible, efficient production.

Dual Wire Feeding : Higher Efficiency, Stronger Welds.

Multi-Material : Stainless steel, carbon steel, aluminum; stable welding from thin to medium-thick plates.

Smart Wire Feeding : Single or dual wire ensures uniform, strong welds.

Energy-Saving & Safe : Low power consumption, touch operation, multiple protections for reliable performance.



Specification

System & Power	Rated Input Voltage	220V 1Φ, 50/60Hz	Welding Performance	Torch Brand	RelFar
	Rated Input Power	16kW		Wobble Scan Type	Dual Oscillating Welding Head
	Max Power Consumption	< 8.5kW		Wobble Type	— ○ ∞ ∂ ⊙ △
	Control System	RelFar System		Energy Storage Welding Mode	-
	Functional Mode	Welding / Cutting / Cleaning / Rust Removal		Wobble Length / Width	0~5mm
	Control Interface	7-inch Touch Screen		Cable Length	10M
Laser Performance	Laser Source Brand	Raycus	Wire Feeding	Torch Weight	≤ 1.0kg
	Fiber Connector	QBH		Wire Feeder	Dual
	Rated Laser Output Power	2000W ±50		Wire Diameter	0.8/1.0/1.2/1.6mm
	Output Laser Wavelength	1080 ±5nm	Cooling	Chiller Brand	S&A
	Operation Mode	Continuous / Pulse / Spot		Cooling Method	Dual-temp dual-control water cooling
	Safety Certification	CE		Assist Gas	Argon / Nitrogen
	Laser Safety Class	Class 4		Gas Input Pressure	≤ 1.0MPa



System & Power	Rated Input Voltage	220V 1Φ, 50/60Hz	Welding Performance	Torch Brand	RelFar
	Rated Input Power	16kW		Wobble Scan Type	Dual Oscillating Welding Head
	Max Power Consumption	< 8.5kW		Wobble Type	—○∞⋈⊙△
	Control System	RelFar System		Energy Storage Welding Mode	-
	Functional Mode	Welding / Cutting / Cleaning / Rust Removal		Wobble Length / Width	0~5mm
	Control Interface	7-inch Touch Screen		Cable Length	10M
Laser Performance	Laser Source Brand	Raycus	Wire Feeding	Torch Weight	≤ 1.0kg
	Fiber Connector	QBH		Wire Feeder	Dual
	Rated Laser Output Power	2000W ±50		Wire Diameter	0.8/1.0/1.2/1.6mm
	Output Laser Wavelength	1080 ±5nm	Cooling	Chiller Brand	S&A
	Operation Mode	Continuous / Pulse / Spot		Cooling Method	Dual-temp dual-control water cooling
	Safety Certification	CE		Assist Gas	Argon / Nitrogen
	Laser Safety Class	Class 4		Gas Input Pressure	≤ 1.0MPa